


AS07NS2HRA
AS09NS2HRA
AS12NS2HRA
AS18NS2HRA
AS24NS2HRA

NEW

AS07NS3HRA
AS09NS3HRA
AS12NS3HRA
AS15NS3HRA
AS18NS3HRA
AS24NS3HRA




7K



AS07NS2HRA
AS07NS3HRA

9K



AS09NS2HRA
AS09NS3HRA

12K



AS12NS2HRA
AS12NS3HRA

comando di serie (NS2)



YR-HD01

15K

NEW



AS15NS3HRA
(applicabile solo a unità esterne
1:3 - 1:4 - 1:5 escluso il dual)

18K



AS18NS2HRA
AS18NS3HRA

24K



AS24NS2HRA
AS24NS3HRA

comando di serie (NS3)

NEW



YR-HG02

Modello	UI	(NS2)	AS07NS2HRA	AS09NS2HRA	AS12NS2HRA		AS18NS2HRA	AS24NS2HRA
Codice commerciale	UI		2501300AL	2501301AL	2501302AL		2501305AL	2501306AL
Modello	UI	(NS3)	AS07NS3HRA	AS09NS3HRA	AS12NS3HRA	AS15NS3HRA	AS18NS3HRA	AS24NS3HRA
Codice commerciale	UI		2501300BL	2501301BL	2501302BL	2501304BL	2501305BL	2501306BL
Dati prestazionali								
Potenza resa RAFF	nom (min-max)	kW	2	2,7 (0,8-3,4)	3,6 (1-4,2)	4,4 (1,3-5)	5,2 (1,3-6,8)	7 (2,2-8,5)
Potenza resa RISC	nom (min-max)	kW	2,3	2,8 (1-4,6)	3,7 (1,1-5,4)	5,4 (1,4-6,0)	5,8 (1,4-6,9)	7,5 (2,4-9,8)
Pdesign RAFF	capacità (35°)	kW	2,7	2,7	3,6	4,4	5,2	7
Pdesign RISC	capacità (-10°)	kW	2,5	2,4	3,2	3,5	4,9	5,6
Alimentazione		V-Ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50	230-1-50	230-1-50
Volume aria trattato		m³/h	600	600	650	700	900	1200
Unità interna								
Potenza sonora		dB	52	52	54	55	57	62
Pressione sonora		dB(A)	38/33/26/20	38/33/26/20	39/34/27/21	40/35/31/22	44/40/35/28	47/43/37/30
Dimensioni	L x P x H	mm	855x204x280	855x204x280	855x204x280	900x210x310	997x235x322	1115x248x336
Peso netto		kg	10	10	10	11,5	13	16
Dati idraulici								
Tubazione liquido Ø		mm	6,35	6,35	6,35	6,35	9,52	9,52
Tubazione gas Ø		mm	9,52	9,52	9,52	9,52	12,7	15,88